

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR LETTERS PATENT

\* \* \* \* \*

FUEL CELL POWER SYSTEMS AND METHODS OF  
CONTROLLING A FUEL CELL POWER SYSTEM

\* \* \* \* \*

INVENTORS

WILLIAM A. FUGLEVAND, P.E.  
DR. SHIBLIHANNA I. BAYYUK, Ph.D.  
GREG A. LLOYD  
PETER D. DEVRIES  
DAVID R. LOTT  
JOHN P. SCARTOZZI

ATTORNEY'S DOCKET NO. WA23-015

TOP SECRET

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24

**FUEL CELL POWER SYSTEMS AND METHODS OF  
CONTROLLING A FUEL CELL POWER SYSTEM**

**RELATED PATENT DATA**

The present application is a continuation-in-part of U. S. Patent Application Serial No. 09/108,667, filed on July 1, 1998, which was a continuation-in-part of U.S. Patent Application Serial No. 08/979,853, filed on November 20, 1997.

**TECHNICAL FIELD**

The present invention relates to fuel cell power systems and methods of controlling a fuel cell power system.

**BACKGROUND OF THE INVENTION**

Fuel cells are known in the art. The fuel cell is an electrochemical device which reacts hydrogen, and oxygen, which is usually supplied from the ambient air, to produce electricity and water. The basic process is highly efficient and fuel cells fueled directly by hydrogen are substantially pollution free. Further, since fuel cells can be assembled into stacks of various sizes, power systems have been developed to produce a wide range of electrical power output levels and thus can be employed in numerous industrial applications.

Although the fundamental electrochemical processes involved in all fuel cells are well understood, engineering solutions have proved elusive for making certain fuel cell types reliable, and for others economical.

In the case of polymer electrolyte membrane (PEM) fuel cell power systems reliability has not been the driving concern to date, but rather the installed cost per watt of generation capacity has. In order to further lower the PEM fuel cell cost per watt, much attention has been directed to increasing the power output of same. Historically, this has resulted in additional sophisticated balance-of-plant systems which are necessary to optimize and maintain high PEM fuel cell power output. A consequence of highly complex balance-of-plant systems is that they do not readily scale down to low capacity applications. Consequently, cost, efficiency, reliability and maintenance expenses are all adversely effected in low generation applications.

It is well known that single PEM fuel cells produce a useful voltage of only about 0.45 to about 0.7 volts D.C. per cell under a load. Practical PEM fuel cell plants have been built from multiple cells stacked together such that they are electrically connected in series. It is further well known that PEM fuel cells can operate at higher power output levels when supplemental humidification is made available to the proton exchange membrane (electrolyte). In this regard, humidification lowers the resistance of proton exchange membranes to proton flow. To achieve this increased humidification, supplemental water can be introduced into the hydrogen or oxygen streams by various methods, or more directly to the proton exchange membrane by means of the physical phenomenon known as of wicking, for example. The focus of investigations, however, in recent years has been to develop membrane

1 electrode assemblies (MEA) with increasingly improved power output  
2 when running without supplemental humidification. Being able to run  
3 an MEA when it is self-humidified is advantageous because it decreases  
4 the complexity of the balance-of-plant with its associated costs.  
5 However, self-humidification heretofore has resulted in fuel cells running  
6 at lower current densities and thus, in turn, has resulted in more of  
7 these assemblies being required in order to generate a given amount of  
8 power.

9 While PEM fuel cells of various designs have operated with  
10 varying degrees of success, they have also had shortcomings which have  
11 detracted from their usefulness. For example, PEM fuel cell power  
12 systems typically have a number of individual fuel cells which are  
13 serially electrically connected (stacked) together so that the power  
14 system can have a increased output voltage. In this arrangement, if  
15 one of the fuel cells in the stack fails, it no longer contributes voltage  
16 and power. One of the more common failures of such PEM fuel cell  
17 power systems is where a membrane electrode assembly (MEA) becomes  
18 less hydrated than other MEAs in the same fuel cell stack. This loss  
19 of membrane hydration increases the electrical resistance of the effected  
20 fuel cell, and thus results in more waste heat being generated. In turn,  
21 this additional heat dries out the membrane electrode assembly. This  
22 situation creates a negative hydration spiral. The continual overheating  
23 of the fuel cell can eventually cause the polarity of the effected fuel  
24 cell to reverse such that it now begins to dissipate electrical power

1 from the rest of the fuel cells in the stack. If this condition is not  
2 rectified, excessive heat generated by the failing fuel cell may cause the  
3 membrane electrode assembly to perforate and thereby leak hydrogen.  
4 When this perforation occurs the fuel cell stack must be completely  
5 disassembled and repaired. Depending upon the design of fuel cell  
6 stack being employed, this repair or replacement may be a costly, and  
7 time consuming endeavor.

8 Further, designers have long sought after a means by which  
9 current densities in self-humidified PEM fuel cells can be enhanced  
10 while simultaneously not increasing the balance-of-plant requirements for  
11 these same devices.

### 12 BRIEF DESCRIPTION OF THE DRAWINGS

13 Preferred embodiments of the invention are described below with  
14 reference to the following accompanying drawings.

15 Fig. 1 is a prospective view of one embodiment of a fuel cell  
16 power system according to the present invention.

17 Fig. 2 is an illustrative representation of a control system coupled  
18 with components of the fuel cell power system.

19 Fig. 3 is an exploded perspective view of one configuration of a  
20 fuel cell cartridge of the fuel cell power system.

21 Fig. 4 is a schematic representation of one embodiment of  
22 circuitry coupled with plural fuel cells of the fuel cell cartridge.  
23  
24

1 Fig. 5 is a functional block diagram of one configuration of the  
2 control system for the fuel cell power system.

3 Fig. 6 is a functional block diagram of a cartridge analysis slave  
4 controller of the control system coupled with associated circuitry and  
5 components.

6 Fig. 7 is a functional block diagram of an auxiliary valve slave  
7 controller of the control system coupled with associated circuitry and  
8 components.

9 Fig. 8 is a functional block diagram of a fan slave controller of  
10 the control system coupled with associated circuitry and components.

11 Fig. 9 is a functional block diagram of an interface slave  
12 controller of the control system coupled with associated circuitry and  
13 components.

14 Fig. 10 is a functional block diagram of an external port slave  
15 controller of the control system coupled with associated circuitry and  
16 components.

17 Fig. 11 is a functional block diagram of a system analysis slave  
18 controller of the control system coupled with associated circuitry and  
19 components.

20 Fig. 12 is a functional block diagram of a sensor slave controller  
21 of the control system coupled with associated circuitry and components.

22 Fig. 13 is a functional block diagram of an air temperature slave  
23 controller of the control system coupled with associated circuitry and  
24 components.

1 Fig. 14 is a functional block diagram of a shunt slave controller  
2 of the control system coupled with associated circuitry and components.

3 Fig. 15 is a functional block diagram of a switch slave controller  
4 of the control system coupled with associated circuitry and components.

5 Figs. 16-16A are a flow chart illustrating exemplary operations of  
6 a master controller of the control system.

7 Fig. 17 is a flow chart illustrating an exemplary start-up operation  
8 of the master controller.

9 Figs. 18-18A are a flow chart illustrating exemplary error  
10 operations of the master controller.

11 Figs. 19-19B are a flow chart of exemplary operations of the  
12 cartridge analysis slave controller.

13 Figs. 20-20A are a flow chart illustrating exemplary operations of  
14 the auxiliary valve slave controller of the control system.

15 Figs. 21-21A are a flow chart illustrating exemplary operations of  
16 the fan slave controller of the control system.

17 Fig. 22 is a flow chart illustrating exemplary operations of the  
18 interface slave controller of the control system.

19 Fig. 23 is a flow chart illustrating exemplary operations of the  
20 external port slave controller of the control system.

21 Figs. 24-24A are a flow chart illustrating exemplary operations of  
22 the system analysis slave controller of the control system.

23 Fig. 25 is a flow chart illustrating exemplary operations of the  
24 sensor slave controller of the control system.

Fig. 26 is a flow chart illustrating exemplary operations of the air temperature slave controller of the control system.

Fig. 27 is a flow chart illustrating exemplary operations of the shunt slave controller of the control system.

Fig. 28 is a flow chart illustrating exemplary operations of the switch slave controller of the control system.

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

This disclosure of the invention is submitted in furtherance of the constitutional purposes of the U.S. Patent Laws "to promote the progress of science and useful arts" (Article 1, Section 8).

Referring to Fig. 1, one configuration of a fuel cell power system 10 is illustrated. The depicted configuration of fuel cell power system 10 is exemplary and other configurations are possible. As shown, fuel cell power system 10 includes a housing 12 provided about a plurality of fuel cell cartridges 14. Housing 12 defines a subrack assembly in the described embodiment.

Fuel cell power system 10 is configured to utilize one or more of fuel cell cartridges 14. Twelve such fuel cell cartridges 14 are utilized in the embodiment of fuel cell power 10 described herein. As described below, individual fuel cell cartridges 14 include a plurality of fuel cells. In the described configuration, individual fuel cell cartridges 14 include four fuel cells.



Such fuel cells can comprise polymer electrolyte membrane (PEM) fuel cells. In the described embodiment, the fuel cells can comprise membrane electrode assembly (MEA) fuel cells or membrane electrode diffusion assembly (MEDA) fuel cells. Further details of one configuration of fuel cells and fuel cell cartridges 14 are described in a co-pending U.S. Patent Application Serial No. 08/979,853, entitled "A Proton Exchange Membrane Fuel Cell Power System", filed November 20, 1997, naming William A. Fuglevand, Dr. Shiblihan I. Bayyuk, Ph.D., Greg A. Lloyd, Peter D. Devries, David R. Lott, John P. Scartozzi, Gregory M. Somers and Ronald G. Stokes as inventors, assigned to the assignee hereof, having attorney docket number WA23-002, and incorporated herein by reference.

Housing 12 additionally includes an operator interface 16. In the present embodiment, operator interface 16 includes a display 18 and interface switches 20. Operator interface 16 is configured to indicate operation of fuel cell power system 10 and also enable an operator to control various functions of fuel cell power system 10.

Display 18 of operator interface 16 is configured to emit a human perceptible signal, such as visible signals, to indicate operation of fuel cell power system 10. In the depicted embodiment, display 18 comprises a plurality of light emitting diode (LED) bar graph arrays to indicate operational conditions of respective fuel cell cartridges 14. In one configuration, individual bar graph arrays of display 18 indicate high

1 and low voltages of fuel cells within the corresponding fuel cell  
2 cartridge 14.

3 Interface switches 20 permit a user to control operations of fuel  
4 cell power system 10. For example, one interface switch 20 can be  
5 provided to enable a user to turn on fuel cell power system 10. In  
6 addition, another interface switch 20 can include a load enable switch  
7 which permits a user to selectively apply power from fuel cell power  
8 system 10 to a load 22 coupled with the fuel cell power system 10.  
9 Another interface switch 20 can control a cartridge reset function  
10 described below.

11 Referring to Fig. 2, some components of fuel cell power  
12 system 10 are shown. The components are internal and external of  
13 housing 12 of fuel cell power system 10. Internally, only three fuel cell  
14 cartridges 14 are shown for purposes of discussion herein. More fuel  
15 cell cartridges 14 are provided in typical configurations.

16 Fuel cell power system 10 is shown coupled with a remote  
17 device 24. Fuel cell power system 10 is preferably configured to  
18 communicate with remote device 24. An exemplary remote device 24  
19 comprises an off-site control and monitoring station. Fuel cell power  
20 system 10 receives communications from remote device 24 which may  
21 comprise data and commands. Fuel cell power system 10 is also  
22 configured to output data, requests, etc. to remote device 24.

23 The depicted components include the plural fuel cell cartridges 14  
24 and operator interface 16 discussed above. In addition, fuel cell power

1 system 10 includes a control system 30. One configuration of control  
2 system 30 is described below in detail. The illustrated control  
3 system 30 is coupled with a power supply sensor 31 associated with a  
4 power supply 32, and charge circuitry 34. Control system 30 is  
5 additionally coupled with fuel cell cartridges 14 and operator  
6 interface 16. Further, control system 30 is coupled with a  
7 communication port 36, switching device 38 and current sensor 40.  
8 Control system 30 is additionally coupled with a bleed solenoid 42  
9 associated with a bleed valve 43.

10 The depicted fuel cell power system 10 includes a fuel delivery  
11 system 28. Fuel delivery system 28 couples with a fuel supply 23 to  
12 supply fuel to fuel cell cartridges 14. Exemplary fuel comprises  
13 hydrogen gas in the described embodiment. Other fuels may be  
14 possible.

15 The depicted fuel delivery system 28 includes a main valve 47 and  
16 plural auxiliary valves 45 associated with respective fuel cell  
17 cartridges 14. Main valve 47 controls the flow of fuel from fuel  
18 supply 23 into fuel cell power system 10. Auxiliary valves 45 control  
19 the flow of fuel to respective fuel cell cartridges 14. Control system 30  
20 is coupled with plural auxiliary solenoids 44 of associated auxiliary  
21 valves 45. Control system 30 is further coupled with a main  
22 solenoid 46 of associated main valve 47.

23 The depicted fuel cell power system 10 includes an air  
24 temperature control assembly 50. The illustrated air temperature control



configuration with an integral heater has designation TGS 813 available from Figaro Engineering, Inc. Such heaters are preferably provided in a predefined temperature range to assure proper operation. Other configurations of sensors 58, 61 are possible.

An external temperature sensor 59 is provided outside of housing 12 in one embodiment. Control system 30 is also coupled with temperature circuitry 67 associated with temperature sensor 59 to monitor the exterior temperature. Temperature circuitry 67 conditions signals received from temperature sensor 59.

Control system 30 is configured to at least one of control and monitor at least one operation of fuel cell power system 10. During operation, fuel from fuel supply 23 is applied to main valve 47. Main valve 47 is coupled with auxiliary valves 45 as shown. Responsive to control from control system 30, main valve 47 and auxiliary valves 45 apply fuel to respective fuel cell cartridges 14. Responsive to the supply of fuel, and in the presence of oxygen, fuel cell cartridges 14 produce electrical power.

A power bus 60 couples the fuel cell cartridges 14 in series. Power bus 60 is coupled with external terminals 62, 63 which may be connected with an external load 22 (shown in Fig. 1). Terminal 62 provides a positive terminal and terminal 63 provides a negative terminal of fuel cell power system 10.

Air temperature control assembly 50 applies oxygen to the respective fuel cell cartridges 14 via ports 52. Fuel cell cartridges 14

are individually operable to convert chemical energy into electricity. As described below, fuel cartridges 14 individually contain plural fuel cells individually having an anode side and a cathode side. Auxiliary valves 45 apply fuel to the anode sides of the fuel cells. Plenum 51 directs air within the cathode sides of the fuel cells.

Air temperature control assembly 50 preferably provides circulated air within a predetermined temperature range. Such circulated air can be exterior air and/or recirculated air. In the preferred embodiment, air temperature control assembly 50 provides air within plenum 51 within an approximate temperature range of 25 °Celsius to 80 °Celsius.

Upon start-up conditions of fuel cell power system 10, modifying element 53 may be controlled via control system 30 using element control circuitry 41 to either increase or decrease the temperature of air present within plenum 51. Fan 54 operates to circulate the air within plenum 51 to respective fuel cell cartridges 14. Fan control circuitry 48 and fan monitor circuitry 49 are shown coupled with fan 54. Responsive to control from control system 30, fan control circuitry 48 operates to control air flow rates (e.g., speed of rotation) of fan 54. Fan monitor circuitry 49 operates to monitor the actual air flow rates induced by fan 54 (e.g., circuitry 49 can comprise a tachometer for rotational fan configurations).

Control system 30 monitors the temperature of the air within plenum 51 using temperature sensor 55. During operation, heat is generated and emitted from fuel cell cartridges 14. Thus, it may be

1 necessary to decrease the temperature of air within plenum 51 to  
2 provide efficient operation of fuel cell power system 10. Responsive to  
3 control from control system 30, air passage 56 can be utilized to  
4 introduce exterior air into plenum 51 and exhaust air from plenum 51  
5 to ambient.

6 Control system 30 communicates with control circuitry 57 to  
7 control air passage 56. In one embodiment, air passage 56 includes a  
8 plurality of vanes and control circuitry 57 operates to control the  
9 position of the vanes of air passage 56 to selectively introduce exterior  
10 air into plenum 51. The vanes of air passage 56 can preferably be  
11 provided in a plurality of orientations between an open position and a  
12 closed position to vary the amount of exterior fresh air introduced into  
13 plenum 51 or the amount of air exhausted from plenum 51 responsive  
14 to control from control system 30. Air circulated within plenum 51 can  
15 comprise recirculated and/or fresh ambient air.

16 Utilizing temperature sensor 59, control system 30 can also  
17 monitor the temperature of ambient air about housing 12. Control  
18 system 30 can utilize such exterior temperature information from  
19 temperature sensor 59 to control the operation of air passage 56.  
20 Temperature sensor 59 is located adjacent air passage 56 in a preferred  
21 embodiment.

22 As described in further detail below, control system 30 controls  
23 air flow rates of fan 54 using fan control circuitry 48. Fan monitor  
24 circuitry 49 provides air flow rate information to control system 30.

Control system 30 can monitor the total system voltage being delivered via power bus 60 by summing the individual cell voltages. Control system 30 can also monitor the electrical load being delivered via power bus 60 using current sensor 40. With knowledge of the system bus voltage and load, control system 30 can calculate waste thermal power and provide a desired cooling air flow.

More specifically, the efficiency of one or more fuel cells may be determined by dividing the respective fuel cell voltage by 1.23 (a theoretical maximum voltage of a single fuel cell). An average efficiency can be determined for all fuel cells 90 of fuel cell power system 10. The remaining energy (energy not associated to electricity) as determined from the efficiency calculation is waste thermal power. The determined waste thermal power may be utilized to provide a desired cooling air flow. Control system 30 controls the air flow rates of fan 54 depending upon the waste thermal power in accordance with one aspect of the described fuel cell power system 10.

During operation of fuel cell cartridges 14, non-fuel diluents such as cathode-side water and atmospheric constituents can diffuse from the cathode side of the fuel cell through a membrane electrode assembly of the fuel cell and accumulate in the anode side of the fuel cell. In addition, impurities in the fuel supply delivered directly to the anode side of the fuel cell also accumulate. Without intervention, these diluents can dilute the fuel sufficiently enough to degrade performance. Accordingly, the anode side of the individual fuel cells is connected to



1 a bleed manifold 65. Bleed manifold 65 is additionally coupled with  
2 bleed valve 43.

3 Control system 30 selectively operates bleed solenoid 42 to  
4 selectively open and close bleed valve 43 permitting exhaustion of  
5 matter such as entrained diluents and perhaps some fuel via a bleed  
6 exhaust 66 within housing 12. Control system 30 can operate to open  
7 and close bleed valve 43 on a periodic basis. The frequency of  
8 openings and closings of bleed valve 43 can be determined by a number  
9 of factors, such as electrical load coupled with terminals 62, 63, etc.  
10 Although not shown, a fuel recovery system may be coupled with bleed  
11 exhaust 66 to retrieve unused fuel for recirculation or other uses.

12 Following a start-up condition either inputted via interface or from  
13 remote device 24, control system 30 selectively controls switching  
14 device 38 to couple power bus 60 with positive terminal 62. Switching  
15 device 38 can comprise parallel MOSFET switches to selectively couple  
16 power bus 60 with an external load 22.

17 For example, control system 30 may verify when an appropriate  
18 operational temperature within plenum 51 has been reached utilizing  
19 temperature sensor 55. In addition, control system 30 can verify that  
20 at least one electrical characteristic, such as voltage and/or current, of  
21 respective fuel cell cartridges 14 has been reached before closing  
22 switching device 38 to couple power bus 60 with an associated load 22.  
23 Such provides proper operation of fuel cell power system 10 before  
24 coupling bus 60 with an external load 22.

Power supply 32 includes power supplies having different voltage potentials in the described embodiment. For example, power supply 32 can provide a 5-volt supply voltage for operating the digital circuitry of fuel cell power system 10, such as control system 30. Power supply 32 can also provide higher voltage potentials, such as +/- 12 volts for operation of components such as fan 54 within fuel cell power system 10.

Further, power supply 32 can include a battery powering components during start-up procedures. Following start-up procedures, power supply 32 can be coupled with power bus 60 and internal power utilized by fuel cell power system 10 can be derived from electrical power generated from fuel cell cartridges 14. Charge circuitry 34 is provided to selectively charge batteries of power supply 32 utilizing power from power bus 60. Control system 30 is configured to monitor electrical conditions of the batteries and the supplied voltages of power supply 32 using power supply sensors 31. Control system 30 can operate charge circuitry 34 to charge batteries of power supply 32 depending upon such monitoring operations.

Control system 30 is also coupled with communication port 36 providing communications to an external device such as a remote device 24. An exemplary remote device 24 comprises an external control system or monitoring system off-site from fuel cell power system 10. Control system 30 can output data including requests, commands, operational conditions, etc., of fuel cell power system 10

1 using communication port 36. In addition, control system 30 can  
2 receive data including commands, requests, etc., from remote device 24  
3 using communication port 36.

4 Referring to Fig. 3, an exemplary fuel cell cartridge 14 is shown.  
5 Further details of fuel cell cartridge 14 are disclosed in detail in U.S.  
6 Patent Application Serial No. 08/979,853 incorporated by reference  
7 above. The depicted fuel cell cartridge 14 includes a fuel distribution  
8 frame 70 and a force application assembly which includes plural cathode  
9 covers 71 which partially occlude respective cavities housing membrane  
10 electrode assemblies (MEA) or membrane electrode diffusion assemblies  
11 (MEDA) within fuel distribution frame 70. The depicted fuel cell  
12 cartridge 14 includes four fuel cells (individually shown as reference  
13 numeral 90 in Fig. 4). Other configurations are possible.

14 The respective cathode covers 71 individually cooperate or  
15 otherwise mate with each other, and with the fuel distribution frame 70.  
16 Individual apertures 72 which are defined by the cathode cover, define  
17 passageways 73 which permit air from plenum 51 to circulate to the  
18 cathode side of the membrane electrode diffusion assembly contained  
19 within fuel distribution frame 70. The circulation of air through the  
20 fuel cell cartridge 14 is discussed in significant detail in U.S. patent  
21 application Serial No. 08/979,853 incorporated by reference above.

22 Conductive members 63 extend outwardly from a main body of  
23 individual fuel cells within fuel cell cartridge 14. Conductive  
24 members 63 are designed to extend through respective gaps or openings

which are provided in fuel distribution frame 70. Each conductive member 63 is received between and thereafter electrically coupled with pairs of conductive contacts which are mounted on a rear wall of a subrack described in greater detail below.

Fuel cell cartridge 14 is operable to be serially electrically coupled with a plurality of other fuel cell cartridges 14 by way of a subrack which is generally indicated by the numeral 76. Subrack 76 has a main body 77 having top and bottom portions 78, 79, respectively. The top and bottom portions are joined together by a rear wall 80. Elongated channels 81 are individually formed in top and bottom portions 78, 79 and are operable to slidably receive individual spines 74 which are formed on fuel distribution frame 70.

Subrack 76 is made of a number of mirror image portions 85, which when joined together, form the main body 77 of subrack 76. These mirror image portions 85 are fabricated from a moldable dielectric substrate. Power bus 60 is affixed on rear wall 80 of the subrack 90. A repeating pattern of eight pairs of conductive contacts 84 are attached on rear wall 80 and are coupled with power bus 60. Electrical coupling of fuel cells within fuel cell cartridge 14 with power bus 60 is implemented using contacts 84 in the described embodiment.

First and second conduits 86, 87 are also attached to rear wall 80 and are operable to matingly couple in fluid flowing relation to the fuel distribution frame 70. The respective first and second conduits 86, 87

extend through rear wall 80 and connect with suitable external conduits (not shown). First conduit 86 is coupled in fluid flowing relation with fuel supply 23 (Fig. 1) and with anode sides of internal fuel cells. Further, second conduit 87 exhausts from the anode sides of the fuel cells to bleed manifold 65 (Fig. 2).

Individual fuel cell cartridges 14 may be selectively deactivated. For example, fuel cell cartridges 14 are individually physically removable from fuel cell power system 10. Removal of one or more fuel cell cartridges 14 may be desired for maintenance, replacement, etc. of the fuel cell cartridges 14. The remaining fuel cell cartridges 14 and internal fuel cells thereof may continue to supply power to an associated load 22 with one or more of the fuel cell cartridges 14 deactivated.

Individual contacts 84 may be configured to maintain electrical continuity of bus 60 upon physical removal of a fuel cell cartridge 14 from an associated subrack 76. As shown, individual contacts 84 comprise make before break contacts which individually include plural conductive members configured to receive an associated contact 69 of a fuel cell cartridge 14. Individual contacts 69 can comprise a tang or knife. Upon physical removal of fuel cell cartridge 14 and the corresponding terminals 69, conductive members of contacts 84 are mechanically coupled together to maintain a closed circuit within bus 60 intermediate terminals 62, 63. Such maintains a supply of electrical

power to load 22 coupled with terminals 62, 63 during removal of one or more fuel cell cartridges 14 from fuel cell power system 10.

Referring to Fig. 4, a schematic representation of four fuel cells 90 of a fuel cell cartridge 14 is shown. Individual fuel cells 90 have plural contacts 84 as described above. Fuel cells 90 are typically coupled in series using power bus 60. Control system 30 is configured to monitor at least one electrical characteristic of individual fuel cells 90 using analysis circuitry 91 in the described embodiment.

More specifically, analysis circuitry 91 includes a voltage sensor 92 which may be provided electrically coupled with contacts 84 as shown. Such coupling enables voltage sensor 92 to monitor the voltages of the individual respective fuel cells 90. Fuel cells 90 have been observed to typically produce a useful voltage of about 0.45 to about 0.7 volts DC under a typical load.

An exemplary configuration of voltage sensor 92 is implemented as a differential amplifier for monitoring voltages. Voltage sensor 92 is preferably configured to monitor voltage magnitude across individual fuel cells 90 as well as polarity of individual fuel cells 90.

Analysis circuitry 91 can additionally include plural current sensors 94, 97. Individual current sensors may be coupled with contacts 84 of individual fuel cells 90 to monitor current flowing through respective individual fuel cells 90 in an alternative arrangement (not shown). Control system 30 is coupled with current sensors 94, 97

1 and is configured to monitor corresponding respective currents through  
2 fuel cells 90 and outputted to load 22 via bus 60.

3 Current sensor 94 is coupled intermediate one of fuel cells 90  
4 and a coupling with internal power supply 93. Current sensor 94 is  
5 coupled intermediate the coupling with internal power supply 93 and  
6 external terminal 62 coupled with an associated load.

7 Following start-up operations, power for internal use within fuel  
8 cell power system 10 (e.g., power provided to the circuitry of control  
9 system 30) is provided from fuel cell cartridges 14. Internal power  
10 supply 93 extracts current from bus 60 as shown to provide internal  
11 power to fuel cell power system 10.

12 Accordingly, current sensor 94 provides information regarding  
13 current flow through serially coupled fuel cell cartridges 14. Current  
14 sensor 97 provides information regarding current flow to a load coupled  
15 with terminal 62 (i.e., load 22 shown in Fig. 1).

16 Plural switching devices 96 are also provided which correspond to  
17 respective fuel cells 90. Switching devices 96 can be individually  
18 provided intermediate contacts 84 of respective fuel cells 90 as  
19 illustrated. In the depicted configuration, switching devices 96 can  
20 comprise MOSFET devices. Gate electrodes of switching devices 96 are  
21 coupled with control system 30.

22 Control system 30 is operable to selectively shunt electrodes 84  
23 using switching devices 96 corresponding to a desired one or more of  
24 fuel cells 90 to electrically bypass or deactivate such fuel cells 90. For

example, if control system 30 observes that an electrical characteristic (e.g., voltage) of a fuel cell 90 as sensed via sensors 92, 94 is below a desired range, control system 30 can instruct a respective switching device 96 to turn on and shunt the respective fuel cell 90. In addition, individual fuel cells 90 can be selectively shunted using respective switching devices 96 to enhance the performance of fuel cells 90.

In one configuration, fuel cells 90 can be shunted according to a duty cycle. The duty cycle may be adjusted by control system 30 depending upon operation of fuel cell cartridges 14 and fuel cell power system 10. Fuel cells 90 can be shunted by sequential order as determined by control system 30. Shunting is also helpful during start-up operations to generate heat within housing 12 to bring fuel power system 10 up to operating temperature in an expedient manner.

Alternatively, individual fuel cells 90 may be shunted for extended periods of time if control system 30 observes such fuel cells are operating below desired ranges (e.g., low voltage conditions, reverse polarity conditions). Shunting operations are discussed in co-pending U.S. Patent Application Serial No. 09/108,667, entitled "Improved Fuel Cell and Method for Controlling Same", filed on July 1, 1998, naming William A. Fuglevand, Peter D. Devries, Greg A. Lloyd, David R. Lott, and John P. Scartozzi as inventors, assigned to the assignee hereof, having attorney docket number WA23-005, and incorporated herein by reference.



1 Referring to Fig. 5, one configuration of control system 30 is  
2 illustrated. In the depicted arrangement, control system 30 includes a  
3 distributed control system including a plurality of controllers 100-120.  
4 Individual controllers 100-120 comprise programmable microcontrollers in  
5 the described embodiment. Exemplary microcontrollers have trade  
6 designation MC68HC705P6A available from Motorola, Inc. In the  
7 described embodiment, controllers 100-120 individually comprise a  
8 controller configured to execute instructions provided within executable  
9 code. In an alternative configuration, the steps described with reference  
10 to Figs. 16-28 below are implemented within hardware.

11 Individual controllers can include random access memory (RAM),  
12 read only memory (ROM), analog-to-digital (A/D) converters, serial  
13 input/output port (SIOP) communications, timers, digital input/  
14 output (I/O), timer interrupts and external interrupts. Individual  
15 controllers 102-120 have internal digital processing circuitry configured  
16 to execute a set of software or firmware instructions. Such instructions  
17 can be stored within the internal read only memory of the respective  
18 controllers 100-120. Other configurations of control system 30 are  
19 possible.

20 Among other functions, master controller 100 functions as a  
21 communication router to implement communications intermediate master  
22 controller 100 and individual slave controllers 102-120. In the described  
23 embodiment, communications are implemented in a limited full-duplex  
24 mode. Other communication protocols may be utilized.

1 Master controller 100 outputs messages to slave  
2 controllers 102-120. Outputted messages are seen by all slave  
3 controllers 102-120. Individual slaves 102-120 identified by the outgoing  
4 message process the corresponding message. Thereafter, receiving slave  
5 controllers 102-120 can output a message to master controller 100. In  
6 addition, master controller 100 can sequentially poll slave  
7 controllers 102-120 to determine whether such slave controllers 102-120  
8 have communications for master controller 100. Master controller 100  
9 can also supply clock information to slave controllers 102-120 to  
10 establish a common timing reference within control system 30.

11 Individual slave controllers 102-120 perform specific tasks in  
12 control system 30 including a plurality of distributed controllers.  
13 Individual slave controllers 102-120 can monitor specified functions of  
14 fuel cell power system 10 and report to master controller 100. Further,  
15 master controller 100 can direct operations of individual slave  
16 controllers 102-120.

17 Referring to Fig. 6, cartridge analysis slave controller 102 is  
18 coupled with master controller 100 and associated circuitry. In  
19 particular, cartridge analysis slave controller 102 is coupled with analysis  
20 circuitry 91 which is in turn coupled with fuel cells 90 and power  
21 bus 60 as previously described. Utilizing voltage sensor 92 and current  
22 sensor 94 of analysis circuitry 91, cartridge analysis slave controller 102  
23 can monitor electrical characteristics such as the voltage of individual  
24 fuel cells 90 as well as the current through fuel cells 90. Further,

1 cartridge analysis slave controller 102 can monitor current flowing  
2 through power bus 60 to load 22 using current sensor 97 of analysis  
3 circuitry 91. As described below, cartridge analysis slave controller 102  
4 can communicate such electrical characteristics to master controller 100.

5 Referring to Fig. 7, auxiliary valve slave controller 104 is shown  
6 coupled with master controller 100 and auxiliary solenoids 44 and bleed  
7 solenoid 42. In turn, auxiliary solenoids 44 are coupled with auxiliary  
8 valves 45 and bleed solenoid 42 is coupled with bleed valve 43 as  
9 discussed above. Responsive to control communications from master  
10 controller 100, auxiliary valve slave controller 104 is configured to  
11 operate auxiliary solenoids 44 and bleed solenoid 42 to control auxiliary  
12 valves 45 and bleed valve 43, respectively.

13 Referring to Fig. 8, fan slave controller 106 is coupled with fan  
14 control circuitry 48 and fan monitor circuitry 49. As described above,  
15 fan control circuitry 48 and fan monitor circuitry 49 are individually  
16 coupled with fan 54. Upon receiving instruction from master  
17 controller 100, fan slave controller 106 is operable to control operation  
18 of fan 54 using fan control circuitry 48. For example, fan slave  
19 controller 106 controls on/off operational modes of fan 54 and the air  
20 flow rate of fan 54. Using fan monitor circuitry 49, fan slave  
21 controller 106 can monitor operation of fan 54. Fan slave  
22 controller 106 can output fan status information (e.g., RPM for a  
23 rotational fan) to master controller 100.  
24

Referring to Fig. 9, interface slave controller 108 is coupled with master controller 100 and operator interface 16. Master controller 100 supplies operational status information from other slave controllers to interface slave controller 108. Thereafter, interface slave controller 108 can control operator interface 16 to convey such status information to an operator. Exemplary indications can include a light emitting diode (LED) array, bar graph display, audio warning buzzer, etc.

Referring to Fig. 10, external port slave controller 110 is coupled with communication port 36 and memory 37 as well as master controller 100. As described previously, communication port 36 is additionally coupled with a remote device 24. Communication port 36 and memory 37 operate to provide bi-directional communications intermediate external port slave controller 110 and remote device 24. Although memory 37 is shown external of external port slave controller 110, in some configurations such memory 37 can be implemented as internal circuitry of external port slave controller 110.

Memory 37 operates to buffer data passing to remote device 24 or data received from remote device 24 within external port slave controller 110. External port slave controller 110 operates to forward received communications to master controller 100 according to timing of master controller 100. External port slave controller 110 operates to output messages from master controller 100 to remote device 24 using communication port 36 according to an agreed-upon communication

1 protocol intermediate external port slave controller 110 and remote  
2 device 24.

3 Referring to Fig. 11, system slave controller 112 is coupled with  
4 master controller 100 as well as main solenoid 46, charge circuitry 34,  
5 power supply sensors 31, current sensor 40 and element control  
6 circuitry 41. Responsive to control from master controller 100, system  
7 slave controller 112 is configured to control the operation of main  
8 valve 47 using main solenoid 46. Further, responsive to control from  
9 master controller 100, system slave controller 112 can selectively charge  
10 a battery 35 of power supply 30<sup>32</sup> using charge circuitry 34.

11 Slave controller 112 can implement the charging of battery 35  
12 responsive to information from power supply sensors 31. Power supply  
13 sensors 31 provide electrical characteristic information of battery 35 and  
14 internal power sources 39 to system slave controller 112. Internal  
15 power sources 39 of power supply 32 include the 5 Volt DC source  
16 and +/- 12 Volt DC source previously described.

17 Using current sensor 40, system slave controller 112 can monitor  
18 current flowing through power bus 60. Such provides load information  
19 and output power of fuel cell power system 10 to system slave  
20 controller 112. Thereafter, system slave controller 112 can provide such  
21 current and load information to master controller 100.

22 System slave controller 112 is also coupled with element control  
23 circuitry 41 utilized to control modifying element 53. Such is utilized  
24 to control the temperature within plenum 51. Modifying element 53

1 can be controlled to provide circulated air within plenum 51 within a  
2 desired operational temperature range. Modifying element 53 is  
3 advantageously utilized in some start-up situations to bring the  
4 temperature within plenum 51 within the operational range in an  
5 expedient manner.

6 Referring to Fig. 12, sensor slave controller 114 is coupled with  
7 master controller 100, heaters 74, 75, fuel detection circuitry 64 and  
8 temperature circuitry 67. Fuel detection circuitry 64 is associated with  
9 plural fuel sensors 58, 61 provided within housing 12 and plenum 51,  
10 respectively. Temperature circuitry 67 is coupled with temperature  
11 sensor 59 located outside of housing 12. Sensor slave 114 can control  
12 heaters 74, 75 to selectively bring fuel sensors 58, 61 within an  
13 appropriate temperature range for operation.

14 Fuel detection circuitry 64 receives data from fuel sensors 58, 61  
15 and can condition such information for application to sensor slave  
16 controller 114. If fuel is detected using fuel sensors 58, 61, fuel  
17 detection circuitry 64 can process such information and provide such  
18 data to sensor slave controller 114. Such information can indicate the  
19 concentration of fuel detected within housing 12 or plenum 51 using  
20 fuel sensors 58, 61, respectively. Sensor slave controller 114 can in  
21 turn provide such information to master controller 100.

22 Temperature sensor 59 provides information regarding the  
23 temperature of the surroundings of fuel cell power system 10.  
24 Temperature circuitry 67 receives outputted signals from temperature

1 sensor 59 and can condition such signals for application to sensor slave  
2 controller 114 monitoring the external temperature. Sensor slave  
3 controller 114 can provide external temperature information to master  
4 controller 100.

5 Referring to Fig. 13, air temperature slave controller 116 is  
6 coupled with master controller 100 and temperature circuitry 68 and  
7 passage control circuitry 57. Temperature circuitry 68 is associated with  
8 temperature sensor 55 provided within plenum 51. Passage control  
9 circuitry 57 operates to control air passage 56. For example, passage  
10 control circuitry 57 can control the position of vanes of air passage 56  
11 in an exemplary embodiment.

12 Temperature sensor 55 is positioned within plenum 51 to monitor  
13 the temperature of circulated air within plenum 51. Temperature  
14 circuitry 68 receives the sensor information from temperature sensor 55  
15 and conditions the information for application to air temperature slave  
16 controller 116. Thereafter, air temperature slave controller 116 may  
17 operate to output the temperature information to master controller 100.

18 During operation of fuel cell power system 10, air temperature  
19 slave controller 116 operates to control the flow of air into housing 12  
20 using air passage 56 as well as the exhaustion of air within plenum 51  
21 to the exterior of housing 12. Air temperature slave controller 116  
22 controls air passage 56 using passage control circuitry 57 to maintain  
23 the temperature of circulated air within plenum 51 within the desired  
24 operational temperature range. Further, modifying element 63 of

Fig. 11 can be controlled as previously discussed to raise or lower the temperature of the circulated air. Such control of air passage 56 by air temperature slave controller 116 can be responsive to information from temperature sensor 55 and external temperature sensor 59. Further, efficiency information regarding fuel cells 90 can be calculated by air temperature slave controller 116 to determine waste thermal power. Air passage 56 may be controlled responsive to the calculated waste thermal power.

Referring to Fig. 14, shunt slave controller 118 is coupled with master controller 100 and switch control circuitry 95. Plural switching devices 96 are coupled with switch control circuitry 95. As described above, switching devices 96 are provided to implement selective shunting of respective fuel cells 90 of fuel cell cartridges 14. Master controller 100 can be configured to output shunt information to shunt slave controller 118 for selectively shunting using switching devices 96. Alternatively, shunt slave controller 118 can execute internally stored code to provide controlled selective shunting of switching devices 96.

Such shunting operations of fuel cells 90 can be utilized to provide increased power, to expedite start-up procedures, to shunt a faulty fuel cell cartridge 14, and to monitor for fuel leaks in exemplary embodiments. Switch control circuitry 95 is provided to provide conditioning of control signals intermediate shunt slave controller 118 and switching devices 96.



Referring to Fig. 15, switch slave controller 120 is coupled with master controller 100 and switch control circuitry 33 and switch conditioning circuitry 19. Switch control circuitry 33 is coupled with switching device 38 provided in series with power bus 60. Responsive to master controller 100, switch slave controller 120 can instruct switch controller circuitry 33 to control switching device 38. Switching device 38 provides selective coupling of power bus 60 to an external load 22. Such can be utilized to assure proper operation of fuel cell power system 10 prior to coupling power bus 60 with load 22.

Switch slave controller 120 can also monitor the status of operator interface switches 20 which may be set by an operator of fuel cell power system 10. Exemplary switches include power on/off of fuel cell power system 10, enable load, cartridge reset, etc. Switch conditioning circuitry 19 can filter signals provided from switches 20 and provide corresponding information regarding switch position to switch slave controller 120. Thereafter, switch slave controller 120 can output the switch status information to master controller 100.

Referring to Figs. 16-16A, a flow chart illustrating exemplary operations of master controller 100 of control system 30 is shown. Initially, master controller 100 performs a communications check at step S10. Communication checks may be implemented on a periodic interrupt basis to verify communications of master controller 100 and slave controllers 102-120.

At step S12, master controller 100 determines whether a communication error was discovered. If such an error is present, master controller 100 issues a shut down command to slave controllers 102-120 at step S14. Respective slave controllers 102-120 implement shut down operations to bring fuel cell power system 10 into a shut down condition. Interface slave controller 108 can indicate the shut down status using operator interface 16. Further, master controller 100 can instruct external port slave controller 110 to notify remote device 24 of the shut down condition.

Alternatively, if no communication error is present in step S12, master controller 100 instructs system slave controller 112 to open main valve 47 at step S16. In addition, master controller 100 instructs fan slave controller 106 to start fan 54 at step S16. At step S18, master controller 100 instructs auxiliary valve slave controller 104 to open auxiliary valves 45 using auxiliary solenoids 44. Next, master controller 100 issues a command to auxiliary valve slave controller 104 to open bleed valve 43 using bleed solenoid 42 at step S20.

Thereafter, master controller 100 may execute a start-up subroutine as set forth in Fig. 17 at step S22. Following successful execution of the start-up subroutine, master controller 100 outputs a load enable "ready" signal to switch slave controller 120 at step S24. Switch slave controller 120 controls, using switch control circuitry 33, switching device 38 to couple power bus 60 with an external load.

At step S26 of Fig. 16A, master controller 100 extracts data from slave controllers 102-120. More specifically, master controller 100 can receive information from cartridge analysis slave controller 102, auxiliary valve slave controller 104, fan slave controller 106, external port slave controller 110, system slave controller 112, sensor slave controller 114, air temperature slave controller 116 and switch slave controller 120.

Next, master controller 100 proceeds to step S28 where it is determined if a cartridge reset request has been issued. An operator can implement a cartridge reset condition using switches 20. If a cartridge reset is indicated, master controller 100 proceeds to step S30 and issues an on-line command to change the status of all off-line fuel cell cartridges 14 to being on-line. Thereafter, master controller 100 initiates a bleed cycle utilizing auxiliary valve slave controller 104 at step S32. During the bleed cycle, fuel may be applied to individual fuel cell cartridges 14 and the bleed valve 43 can be opened to allow exhaust operations using bleed manifold 65 and bleed exhaust 66.

If no cartridge reset request is indicated at step S28, or after the bleed cycle is initiated at step S32, master controller 100 proceeds to step S34 to determine whether a communication error is present. If a communication error is present, master controller 100 issues a shut down command at step S36.

If no communication error is present at step S34, master controller 100 proceeds to step S38 to execute an error subroutine as described in Figs. 18-18A below. At step S40, master controller 100

1 calculates operating parameters utilizing the data obtained at step S26.  
2 Based upon the calculated operating parameters (e.g., setting of fan 54,  
3 modifying element 53, etc.), master controller 100 sends the system  
4 settings at step S42 to the appropriate slave controllers 102-120.

5 Referring to Fig. 17, a start-up subroutine executable by master  
6 controller 100 is described. Initially, data from sensor slave  
7 controller 114 is analyzed to determine whether the temperature within  
8 plenum 51 is less than 15 °Celsius. If yes, master controller 100 turns  
9 on modifying element 53 utilizing system slave controller 112 at  
10 step S52. Alternatively, master controller 100 instructs systems slave  
11 controller 112 to turn off modifying element 53 if appropriate at  
12 step S54.

13 Thereafter, master controller 100 proceeds to step S56 and  
14 instructs shunt slave controller 118 to set a shunting duty cycle to  
15 maximum. At step S58, master controller 100 again retrieves the  
16 temperature within plenum 51 from air temperature slave controller 116.  
17 At step S58, master controller 100 determines whether the temperature  
18 within plenum 51 is less than 30 °Celsius. If so, master controller  
19 loops at step S58 until the temperature within plenum 51 is equal to  
20 or greater 30 °Celsius. Next, at step S60, master controller 100 can  
21 calculate a new duty cycle for application to shunt slave controllers 118.  
22 Thereafter, master controller 100 returns to the main set of instructions  
23 described in Figs 16-16A.  
24

1 Referring to Figs. 18-18A, a flow chart illustrating exemplary error  
2 operations of master controller 100 is illustrated. Initially, at step S62,  
3 master controller 100 determines whether fan operation is proper.  
4 Master controller 100 observes data from fan slave controller 106 and  
5 outputs a fan error message to interface slave controller 108 at  
6 step S64 if fan operation is not proper. Thereafter, a shut down  
7 command is issued at step S66 to initiate a shut down procedure of  
8 fuel cell power system 10.

9 At step S68, it is determined whether internal power supplies are  
10 operating properly. More specifically, master controller 100 interfaces  
11 with system slave controller 112 to determine whether values monitored  
12 by power supply sensors 31 are within range. If not, master  
13 controller 100 sends a power supply error message to interface slave  
14 controller 108 at step S70. Thereafter, master controller 100 issues a  
15 shut down command at step S72.

16 At step S74, master controller 100 determines whether auxiliary  
17 valve operation is proper. Such is determined by data received from  
18 auxiliary valve slave controller 104 regarding the status of auxiliary  
19 valves 45. This can be additionally performed by monitoring the voltage  
20 of a deactivated fuel cell 90. A zero voltage should result if auxiliary  
21 valve operation is proper. Master controller 100 outputs an auxiliary  
22 valve error message at step S76 to interface slave controller 108 if  
23 operation is not proper. Such error message can thereafter be  
24

1 displayed using operator interface 16. At step S78, master  
2 controller 100 issues a shut down command.

3 Alternatively, master controller 100 proceeds to step S80 and  
4 determines whether a major fuel leak is present. Such is determined  
5 by monitoring data received from sensor slave controller 114 responsive  
6 to the monitoring of fuel sensors 58, 61. If a major fuel leak is  
7 detected, master controller 100 sends a major fuel leak error message  
8 to interface slave controller 108 at step S82. Thereafter, a shut down  
9 command is issued at step S84.

10 If no major fuel leak is determined, master controller 100  
11 proceeds to step S86 to determine whether a minor fuel leak is present.  
12 In one configuration, a major fuel leak may be defined as  $\geq 5000$  ppm  
13 and a minor fuel leak may be defined as 1000-4999 ppm. In some  
14 applications, the ranges may be varied for increased or decreased  
15 sensitivity to fuel.

16 If a minor fuel leak is determined at step S86, master  
17 controller 100 proceeds to step S88 to try to determine if one of fuel  
18 cell cartridges 14 is faulty and the source of the fuel leak.  
19 Accordingly, a first fuel cell cartridge 14 is deactivated at step S88.  
20 Next, master controller 100 attempts to determine whether the fuel leak  
21 is gone. Deactivation of the fuel cell cartridge 14 ceases the supply  
22 of fuel to the fuel cell cartridge 14 using the appropriate auxiliary  
23 valve 45. If it is determined that the fuel leak is gone, an error  
24

1 message is sent at step S92 to interface slave controller 108 for  
2 conveyance to operator interface 16.

3 If the fuel leak remains as determined at step S90, master  
4 controller 100 proceeds to step S94 to reactivate the previously  
5 deactivated fuel cell cartridge 14 and deactivate a subsequent fuel cell  
6 cartridge 14. At step S96, master controller 100 determines whether an  
7 index has led past the last fuel cell cartridge 14. If not, master  
8 controller 100 returns to steps S90-S94 to continue with the minor leak  
9 analysis. Alternatively, master controller 100 proceeds to step S98 and  
10 ignores the minor leak for a specified period of time. Once the  
11 specified period of time has elapsed, and the fuel leak is still present,  
12 master controller 100 can issue a shut down command which will cease  
13 the supply of fuel from fuel supply 23 into housing 12 using main  
14 valve 47.

15 At step S100, master controller 100 determines whether there is  
16 a failed fuel cell cartridge 14. If so, master controller 100 shuts off  
17 the supply fuel to the failed fuel cell cartridge 14 using the appropriate  
18 auxiliary valve 45 at step S102. In addition, a full-time shunt command  
19 for the failed fuel cell cartridge 14 is applied to shunt slave  
20 controller 118 at step S104. At step S106, master controller 100 sends  
21 an error message to interface slave controller 108 for conveyance using  
22 operator interface 16.

23 At step S108, master controller 100 determines whether enough  
24 fuel cell cartridges 14 are currently on-line. In one exemplary

1 arrangement, master controller 100 determines whether less than eight  
2 fuel cell cartridges 14 are on-line. If not enough cartridges are on-line,  
3 master controller 100 sends an error command at step S110 to interface  
4 slave controller 108. Such error message can be conveyed to an  
5 operator using operator interface 16. Next, at step S112, master  
6 controller 100 issues a shut down command for fuel cell power  
7 system 10. If enough fuel cell cartridges 14 are on-line at step S108,  
8 master controller 100 proceeds to the main set of instructions defined  
9 in the flow chart of Figs. 16-16A.

10 Referring to Figs. 19-19B, a flow chart illustrating exemplary  
11 operations of cartridge analysis slave controller 102 is shown. Initially,  
12 at step S120, slave controller 102 indexes to a first fuel cell 90 within  
13 fuel cell power system 10. A transient counter described below is  
14 cleared at step S121. Slave controller 102 obtains a voltage reading of  
15 the indexed fuel cell 90 at step S122. At step S124, slave  
16 controller 102 determines whether the polarity of the indexed fuel  
17 cell 90 is proper. If not, slave controller 102 proceeds to step S126  
18 and sets the indicated fuel cell voltage to zero. Thereafter, the voltage  
19 for the currently indexed fuel cell 90 is posted to a fuel cell array at  
20 step S134.

21 Alternatively, if the polarity of the indexed fuel cell 90 is proper  
22 at step S124, slave controller 102 determines whether the voltage is  
23 proper at step S128. If not, slave controller 102 increments a ride-  
24 through transient counter at step S130. Thereafter, slave controller 102



1 determines whether the transient counter is at a maximum value at  
2 step S132. If not, slave controller 102 returns to step S122. If the  
3 transient counter has reached a maximum value, slave controller 102  
4 proceeds to step S134 to post the voltage to the fuel cell array.

5 At step S136, slave controller 102 determines whether all of the  
6 fuel cells 90 have been indexed. If not, slave controller 102 indexes  
7 to a next fuel cell 90 at step S138 and thereafter returns to step S122.  
8 If all fuel cells 90 have been analyzed using analysis circuitry 91, slave  
9 controller 102 proceeds to step S140 to arrange the fuel cell readings  
10 into readings for respective fuel cell cartridges 14.

11 Next, slave controller 102 proceeds to step S141 to index to a  
12 first of fuel cell cartridges 14. Slave controller 102 then proceeds to  
13 step S142 to determine whether any of the fuel cell cartridges 14 were  
14 previously provided in a down or off-line condition. If so, slave  
15 controller 102 proceeds to step S160 to determine whether the last fuel  
16 cell cartridge 14 has been indexed. Otherwise, slave controller 102  
17 proceeds to step S144 to determine whether a voltage of any of the  
18 fuel cells of a currently indexed fuel cell cartridge 14 have an  
19 unacceptable voltage condition (e.g., low voltage). If so, slave  
20 controller 102 increments a low voltage counter at step S146. Next,  
21 slave controller 102 proceeds to step S148 to determine whether the low  
22 voltage counter is at a maximum value. The maximum value is selected  
23 to provide the unacceptable fuel cell with a chance to recover and  
24 provide an acceptable voltage during a subsequent pass through the flow

chart. If the low voltage counter is at maximum, slave controller 102 proceeds to step S150 to set the currently indexed fuel cell cartridge 14 status as deactivated (e.g., down or off-line). Slave controller 102 instructs master controller 100 to shut off fuel to the currently indexed fuel cell cartridge 14 at step S152. Master controller 100 thereafter instructs auxiliary valve slave controller 104 to shut off fuel to the respective fuel cell cartridge 14. At step S154, master controller 100 additionally outputs a command to shunt slave controller 118 to shunt the appropriate fuel cell cartridge 14. Also, master controller 100 can output the message to interface slave controller 108 to convey the status of the currently indexed fuel cell cartridge 14 using operator interface 16.

If the currently indexed fuel cell cartridge 14 has a proper voltage as determined at step S144, slave controller 102 proceeds to step S145 to clear the low voltage counter. Slave controller 102 associates the fuel cells with respective low voltage counter values. The low voltage counter for a given fuel cell previously determined to be unacceptable during the current pass through the flow chart is cleared at step S145 if the voltage is deemed acceptable at step S144.

Slave controller 102 proceeds to step S156 to post high and low voltages of the fuel cells of the currently indexed fuel cell cartridge 14 to memory. At step S158, slave controller 102 outputs the high and low voltage information of the fuel cells of the fuel cell cartridge 14 to master controller 100. Master controller 100 processes the high and

low voltages for the fuel cell cartridge 14 and can instruct interface slave controller 108 to display or otherwise convey the voltages to an operator using operator interface 16.

At step S160, slave controller 102 determines whether the last fuel cell cartridge 14 has been indexed. If not, slave controller 102 indexes to a next fuel cell cartridge 14 at step S162 and thereafter returns to step S142. If the last fuel cell cartridge 14 has been indexed at step S160, slave controller 102 proceeds to step S164 to determine whether too many fuel cell cartridges 14 are down (e.g., less than seven fuel cell cartridges 14 are down or off-line). If so, slave controller 102 sends an appropriate message to master controller 100 at step S166.

At step S168, slave controller 102 monitors for the reception of messages from master controller 100. If a message is received, slave controller 102 processes the incoming message at step S170. At step S172, slave controller 102 can transmit fuel cell data and any messages. Thereafter, slave controller 102 returns to step S120 to index the first fuel cell 90 to repeat the analysis.

Referring to Figs. 20-20A, a flow chart illustrating exemplary operations of auxiliary valve slave controller 104 is shown. Initially, slave controller 104 performs a communication check at step S180 to assure proper communications with master controller 100. At step S182, slave controller 104 listens for a start-up signal from master controller 100. At step S184, it is determined whether the appropriate start-up signal has been received. Once the start-up signal is received,

1 slave controller 104 instructs auxiliary solenoids 44 to open respective  
2 auxiliary valves 45 at step S186. At step S188, slave controller 104  
3 commences to perform a bleed procedure wherein slave controller 104  
4 instructs bleed solenoid 42 to open bleed valve 43 for a defined length  
5 of time.

6 At step S190, slave controller 104 reads data and messages from  
7 master controller 100. Slave controller 104 determines whether the  
8 master is off-line at step S192. If so, slave controller 104 closes  
9 auxiliary valves 45 at step S194. Otherwise, slave controller 104  
10 proceeds to step S196 to determine whether a shut down request has  
11 been issued by master controller 100. If so, slave controller 104  
12 proceeds to step S194. Otherwise, slave controller 104 proceeds to  
13 step S198 to determine whether a change in status of any fuel cell  
14 cartridges 14 has been made. If so, slave controller 104 controls  
15 respective auxiliary valves 45 at step S200 to either supply fuel if the  
16 corresponding fuel cell cartridge 14 is on-line, or cease supply of fuel  
17 if the fuel cell cartridge 14 has been taken off-line.

18 At step S202, slave controller 104 monitors to determine whether  
19 it is time for a bleed cycle. Slave controller 104 can be configured to  
20 periodically implement a bleed cycle using bleed solenoid 42 and bleed  
21 valve 43 according to a bleed timer. If it is time for a bleed cycle,  
22 slave controller 104 proceeds to step S204 to reset the bleed timer and  
23 thereafter commence a bleed procedure at step S206. As shown, slave  
24



Referring to Fig. 22, a flow chart illustrating exemplary operations of interface slave controller 108 is shown. Initially, slave controller 108 proceeds to step S240 to perform a communications check with master controller 100. Thereafter, slave controller 108 outputs appropriate message information to operator interface 16 for conveyance to an operator. In the described embodiment, operator interface 16 displays the message information received from master controller 100.

Slave controller 108 listens for updates to operator interface 16 at step S244. At step S246, it is determined whether master controller 100 is off-line. If so, slave controller 108 sends an error message to operator interface 16 to indicate master controller 100 is off-line. Otherwise, slave controller 108 proceeds to step S250 to determine whether there was a change in the status of operator interface 16. If not, slave controller 108 proceeds to step S244 and listens for updates for operator interface 16. If a change in interface status is indicated at step S250, slave controller 108 proceeds to step S252 to update operator interface 16.

Referring to Fig. 23, a flow chart illustrating exemplary operations of external port slave controller 110 is illustrated. Initially, slave controller 110 performs a communications check with master controller 100 at step S260. Thereafter, slave controller 100 reads any input communication from remote device 24 and communication port 36. At step S264, slave controller 110 sends any received communications to master controller 100. At step S266, slave controller 110 receives

any communications from master controller 100. Slave controller 110 proceeds to forward any communications to communication port 36 and remote device 24 at step S268.

Referring to Figs. 24-24A, a flow chart illustrating exemplary operations of system slave controller 112 is shown. Initially, at step S270, slave controller 112 performs a communications check with master controller 100. Next, slave controller 112 can read status information from power supply sensors 31 and current sensor 40 at step S272. At step S274, it is determined by slave controller 112 whether the inputted status values are within appropriate ranges. If not, slave controller 112 can generate an error message at step S276 for application to master controller 100.

Otherwise, slave controller 112 proceeds to step S278 and listens for a main valve open command from master controller 100. At step S280, it is determined whether the open valve command was received. Once the open valve command is received, slave controller 112 proceeds to step S282 to activate main valve 47 using main solenoid 46. At step S284, slave controller 112 listens for a shut down command from master controller 100.

Proceeding to step S286, slave controller 112 determines whether the master controller 100 is off-line. If so, slave controller 112 proceeds to step S296 to shut off power supply 32 and main valve 47 using main solenoid 46. If master controller 100 is on-line, slave controller 112 proceeds to step S288 to again read status values from

power supply sensors 31 and current sensor 40. Slave controller 112 can control charge circuitry 34 to charge battery 35, if necessary, at step S290 responsive to the values read at step S288.

At step S292, slave controller 112 determines whether the values are within the appropriate ranges. If not, slave controller 112 proceeds to step S294 to generate an error message for application to master controller 100. Otherwise, at step S296, slave controller 112 monitors for the presence of a shut down command or request from master controller 100. If no shut down command is issued, slave controller 112 returns to step S284. If a shut down request or command is received at step S296, slave controller 112 proceeds to step S296 to shut off main valve 47 using main solenoid 46 as well as turn off power supply 32.

Referring to Fig. 25, a flow chart illustrating exemplary operations of sensor slave controller 114 is shown. Initially, at step S300, slave controller 114 performs a communication check with master controller 100. At step S302, slave controller 114 controls heaters 74, 75, if necessary, to bring associated fuel sensors 58, 61 within proper operating temperature ranges. Thereafter, slave controller 114 is configured to read information from fuel detection circuitry 64 and corresponding fuel sensors 58, 61.

Responsive to reading the fuel sensor values, slave controller 114 determines at step S306 whether a major leak was detected. If so, slave controller 114 forwards an appropriate major leak message to



1 master controller 100 at step S308. At step S310, the fuel sensor  
2 values are analyzed to determine whether a minor leak was detected.  
3 If so, slave controller 114 sends an appropriate minor leak message to  
4 master controller 100 at step S312.

5 At step S314, slave controller 114 reads external temperature  
6 information from temperature circuitry 67 and associated temperature  
7 sensor 59. At step S316, slave controller 114 sends external  
8 temperature values to master controller 100.

9 Referring to Fig. 26, a flow chart illustrating exemplary operations  
10 of air temperature slave controller 116 is shown. Initially, slave  
11 controller 116 performs a communication check with master  
12 controller 100 at step S320. Thereafter, slave controller 116 reads  
13 temperature values from temperature circuitry 68 and associated  
14 temperature sensor 55 located within air plenum 51. At step S324,  
15 slave controller 116 reads a temperature set point as calculated from  
16 master controller 100.

17 At step S326, slave controller 116 sets recirculation using air  
18 passage 56 and fan 54 to maintain a set point temperature. Slave  
19 controller 116 outputs the air temperature of plenum 51 as determined  
20 by temperature sensor 55 to master controller 100 at step S328.

21 Referring to Fig. 27, a flow chart illustrating exemplary operations  
22 of shunt slave controller 118 is shown. Initially, at step S330, slave  
23 controller 118 performs a communication check with master  
24

1 controller 100. At step S332, slave controller 118 reads data from  
2 master controller 100.

3 At step S334, it is determined whether there was a change in  
4 status of the fuel cell cartridges 14. If so, slave controller 118  
5 proceeds to step S336 to determine whether there is a change of any  
6 of the fuel cell cartridges 14 to an off-line condition. If not, the  
7 appropriate switching device 96 for the respective fuel cell cartridge 14  
8 is latched to an off position at step S338. Alternatively, slave  
9 controller 118 proceeds to step S340 to latch the appropriate switching  
10 device 96 for the respective fuel cell cartridge 14 in an on position.

11 Following processing of steps S338 or S340, or alternatively if  
12 there is no change in status of fuel cell cartridges 14 as determined at  
13 step S334, slave controller 118 proceeds to step S342 to cyclically shunt  
14 fuel cells 90 within fuel cell cartridges 14 as described in detail in U.S.  
15 Patent Application Serial No. 09/108,667 incorporated by reference  
16 above.

17 Referring to Fig. 28, a flow chart illustrating exemplary operations  
18 of switch slave controller 120 is shown. Slave controller 120 performs  
19 a communication check with master controller 100 at step S350.  
20 Thereafter, slave controller 120 reads switch status information from  
21 switches 20 and switch conditioning circuitry 19 at step S352. At  
22 step S354, slave controller 120 reads load enable status information from  
23 master controller 100.  
24

Slave controller 120 determines whether a power off request was received from master controller 100 at step S356. If yes, slave controller 120 proceeds to step S358 to send a shut down message to master controller 100. Otherwise, slave controller 120 proceeds to step S360. Slave controller 120 determines whether a load enable request was provided from switches 20. If so, slave controller 120 proceeds to step S362 to determine whether master controller 100 has indicated fuel cell power system 10 is ready to provide power as determined in step S354. If so, slave controller 120 proceeds to step S364 to enable switching device 38.

At step S366, slave controller 120 determines whether the master controller 100 is in an off-line condition. If so, slave controller 120 disables switching device 38 at step S368. Otherwise, slave controller 120 proceeds to step S370 to determine whether a cartridge reset has been indicated from switches 20. If so, slave controller 120 proceeds to send a cartridge reset message to master controller 100 at step S372. Slave controller 120 then returns to step S352 to read switch status from switch conditioning circuitry 19 and associated switches 20 at step S352.

In compliance with the statute, the invention has been described in language more or less specific as to structural and methodical features. It is to be understood, however, that the invention is not limited to the specific features shown and described, since the means herein disclosed comprise preferred forms of putting the invention into

1 effect. The invention is, therefore, claimed in any of its forms or  
2 modifications within the proper scope of the appended claims  
3 appropriately interpreted in accordance with the doctrine of equivalents.  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24

PATENT 3720660